



- Power Requirements** : 110/220V. 60/50Hz. AC (%±10) 24V. DC at standby ~11W. max. ~60W.
- Dimensions** : 1210 x 280 + Arm length (470 mm) x 1000 mm
- Arms** : (Automatic Drop Arm) Retractable Ø40mmx1,2mm 304-Grade (Opt. 316-Grade) (Opt. anodised hard aluminium). Arms can be dismantled or mounted one by one separately.
- Body Features** : 304-Grade (Opt. 316-Grade) Stainless steel with brushed (Opt. Satin) surface. Protected against water for outdoors use. Half- cylindrical rounded legs.
- Indicator Features** : Decorative indicators on both legs in double stripe form.
- Operating Temperature, Humidity, IP Rating, MCBF** : -20°C - +68°C (-50°C with optional heater unit) / RH 95% non-condensing / IP 54 Outdoor rated (Opt. IP 56) / 1M Cycles



# 702 R N1 TECHNICAL SPECIFICATIONS

- Control System** : All inputs are opto-coupler protected. Controlled by dry contact or grounding input. Compatible with all access control systems that provide dry contact or grounding outputs. Optional RS232/RS485/TCP IP control module is available.
- Operation** : Motorized bi-directional passage system (Opt. Manual System); the system unlocks upon receiving input and motor is activated by a gentle push on the arm to allow passage.
- Output Data** : The system provides dry contact passage feedback by relays.
- Emergency Mode** : (Standard: Fail Safe); in case of power failure or emergency, the arm drops automatically to allow free passage (Opt. Fail Secure).
- Flow Rate** : Capacity of Mechanism (Motorized System):~48 passages/minute;  
Nominal ~25 - 46 passage-per-minute (Recommended reference figure)
- ❖ **Explanatory Notes:**
    - The above given figures are approximate for one person per walkway or lane.
    - The system allows the new passage authorisation in less than ~0, 3 seconds. After the passage authorization, the total passage time depends on the pushing and passage speed of the people.
    - Utilisation of different access control units can change the flow rate.
- Standard Features** : Direction and status indicators on top and sides, motorized mechanism, (Automatic Drop) retractable arm.
- Optional Accessories and Applications** : Remote control units, interface unit for PC, RS485, RS232 and LAN, counter, audio-messaging system, alarm sensor, heater positive unit, coin slot/intelligent coin system and coin box, card reader pole, pipe barrier (Separator), base plate, customised top covers to accommodate various accessories.

*\*Design and specifications are subject to change without notice.*