

## Smart and Stable POS System NBP-150

Modularized and removable design allows you to customize your high-end POS system based on your need. Single screen, dual screen and VFD display, etc. NBP-150 provides whatever you want.



### SOLUTION RETAIL



*To satisfy service demands, retail and hospitality industry require high-performance POS systems with flexible mount installation options to suit diverse application environments.*

Take advantage of the opportunity to big customers at POS system with SEWOO products. The latest POS system NBP-150 makes sure of its superior configurability, scalability, and power.





Easy to change not only customer display or 2nd screen but also MSR and Ibutton without screwdriver.

Rotate 180°

2\*20 VFD or LCD customer monitor

MSR and RFID or I-Button

2\*USB Port



Republic of Korea [Head Office/R&D Center]

28-6, Gajangsaneopdong-ro, Osan-si, Gyeonggi-do, 18103, Republic of Korea

T. +82-31-8077-5000 / F. +82-31-624-5310 E. sales@miniprnter.com / H. www.miniprnter.com

## NBP-150 POS System

### SPECIFICATIONS

#### CPU

- Intel Celeron J4125 4C/4T 2.0GHz
- Intel i3 : intel® dual core, 4T, 5<sup>th</sup>/6<sup>th</sup>/7<sup>th</sup>
- Intel i5 : intel® dual core, 4T, 5<sup>th</sup>/6<sup>th</sup>/7<sup>th</sup>

#### OS

- Supporting System : POSReady 7, Windows 10 IoT Enterprise

#### MAIN

- Memory : DDR3 4GB (up to 8GB)
- Storage : 2.5" SATA 64G or MSATA (UP TO 512G or HDD 500G)

#### PRIMARY DISPLAY

- Lcd : 15" TFT LED
- Resolution : 1024 x 768
- Customer Display : VFD 220 Customer Display / LCD 2 line x 20 characters / LED Display characters: Single line display Support 8 number only
- Touch Screen : 15" Bezel-Free True-Flat Protective Capacitive Touch Screen
- Secondary Display : 10.1" LCD, 15" LCD

#### INTERFACE

- Intel J4125 : VGA (1), HDMI (1) RS232 (2), RJ45 (1), USB (6), RJ11 (1)
- Intel i3 / i5 : VGA (1), HDMI (1) RS232 (2), RJ45 (1), USB (6)
- Audio : 1 \* Mic-in, 1 \* Line-out

#### POWER

- DC-IN : Input AC 100~240V / 50~60hz, Output DC 12V/5A

#### ENVIRONMENT

- Temperature : (Operating) 0~40° / (Storage) -20°~60°
- Dimension : 220mm x 190mm x 350mm (WxDxH)

#### SIZE

- Weight : 7kg

#### OPTIONAL

- MSR : ISO 1,2,3 Tracks
- iButton : Dallas Key RS232 I/F
- Finger Reader
- RFID(13.56Mhz)
- 2x20 VFD
- 2x20 LCD
- LED Customer display
- 10,1inch or 15inch Second display
- Speaker

#### RELIABILITY

- Certifications : CE, RoHS, FCC

Rev. April 2021

\* Specifications are subject to change without prior notice.