

■ System Options & Accessories

ENCLOSURE

KE-8

Keri's KE-8 enclosure facilitates the mounting of four PXL-500's with SB-593 option boards or four NXT controllers in a convenient, secure metal enclosure (wall or IT rack-mountable).



AUTO-USB NETWORKING

USB-A

Provides the advantages of a TCP/IP-based system in an easy-to-configure, plug & play format. Using standard Ethernet components and wiring, AutoUSB requires no Ethernet knowledge or approval from most customers' IT Departments.




- Connects NXT Hardware via USB Port on PC
- Plug-and-Play connectivity and functionality
- All controller addressing done automatically
- Greatly simplifies setup and configuration for systems up to 256 Readers

UNIVERSAL DESKTOP ENROLLMENT READER

RDR-ENR1

Keri's desktop card-reader combines proximity and contactless technologies into a universal desktop reader for presentation enrollment at a computer location.



- Integrated with Doors.NET software
- Reads a variety of popular 3rd party 125 kHz proximity cards and 13.56 MHz smart cards
- Plugs directly into a PC's USB port

SERIAL COMMUNICATIONS MODULE

SW-SCM

Connects PXL-500 Master Controller to PC's USB port, and comes with a 15'ft cable (4.57 meters)



POWER SUPPLIES

Keri offers several power supplies perfectly matched to the NXT, PXL, and Entraguard hardware products.

KPS-11

+12VDC@10A

Especially useful for IT rooms and other applications with centrally located controllers.



KPS-4-1 without enclosure

KPS-5-1 with enclosure

+12VDC@2.5A

Powers up to 4 doors of either PXL or NXT hardware.



LAN-PORT CONNECTOR

LAN-520-AESP

For connecting PXL-500 Master Controller to host computer via TCP/IP (shown mounted with NC-485X)



ETHERNET CONVERTER

NC-485 to RS-485

Pairs with and mounts on LAN-520-AESP to use Ethernet connectivity to bridge PXL-500 RS-485 network

