

4-in-1 Multi-Purpose Siren/Strobe

SH-816S-SMQ/R Siren/Strobe/Message/PA – Red

SH-816S-SMQ/B Siren/Strobe/Message/PA - Blue

SH-816S-SMQ/C Siren/Strobe/Message/PA - Clear

SH-816S-SMQ/A Siren/Strobe/Message/PA - Amber

SH-816S-BMQ Siren/Message/PA

The ENFORCER 4-in-1 Multi-Purpose Siren/Strobe is multiple communication and signaling devices in one: siren, internal message, broadcast, and (SH-816S-SMQ only) an LED strobe. Depending on application it can sound a siren, playback your pre-recorded message/custom sound from internal memory, and/or be used as a PA broadcast system.



Features

- Multiple devices in one siren/strobe, internal custom emergency message, and PA system
- Multiple notification types strobe, siren, or audio (pre-recorded or broadcast)
- Multiple audio sources siren, on-board MP3/WAV, external public address (PA) system
- Upload your own warning message (MP3 or WAV format, up to 2MB) via micro-USB port
- 9~15 VDC and low current draw
- 2 Alarm inputs input 1 triggers 115dB siren, input 2 overrides input 1 to play custom message
- 20W Speaker for PA broadcast input (input not to exceed 2V, broadcast interrupts both alarms)
- Built-in tamper alarm output
- Weatherproof for outdoor/indoor use, IP65

Specifications

Model SH-816-BMQ SH-816-SMQ/x* Type Siren/message/broadcast Siren/message/broadcast + strobe Operating voltage 9~15 VDC Alarm inputs 2x Ground trigger – input 2 (custom message/sound) overrides input 1 (siren) Audio in Audio input voltage cannot exceed 2V Current draw (max.) Siren Strobe N/A 50mA@12VDC Max.) Both N/A 1050mA@12VDC Siren volume 115dB Speaker rating 20W Peak Custom message WAV or MP3 format, up to 2MB Upload interface Micro-USB Strobe flash rate N/A 60 per minute Tamper output 100mA@30 VAC/VDC IP Rating IP65 Operating temperature -4°~131° F (-20°~55° C) Housing Polycarbonate plastic Dimensions 61/6"x415/16"x41/2" (155x178x115 mm) Weight 1-lb 13-oz (812g) 2-lb 2-oz (957g)	<u> </u>				
Siren/message/broadcast	Model		SH-816-BMQ	SH-816-SMQ/x*	
Alarm inputs	Туре		Siren/message/broadcast	_	
Audio in Audio input voltage cannot exceed 2V Current draw Siren Strobe N/A 50mA@12VDC (max.) Both N/A 1050mA@12VDC Siren volume 115dB Speaker rating 20W Peak Custom message WAV or MP3 format, up to 2MB Upload interface Micro-USB Strobe flash rate N/A 60 per minute Tamper output 100mA@30 VAC/VDC IP Rating IP65 Operating humidity 0~98% Operating temperature -4°~131° F (-20°~55° C) Housing Polycarbonate plastic Dimensions 6¹/8"x4¹5/16"x4¹/2" (155x126x115 mm) 6¹/8"x7"x4¹/2" (155x178x115 mm)	Operating voltage		9~15 VDC		
Current draw (max.) Siren Strobe N/A 50mA@12VDC (max.) Both N/A 1050mA@12VDC Siren volume 115dB Speaker rating 20W Peak Custom message WAV or MP3 format, up to 2MB Upload interface Micro-USB Strobe flash rate N/A 60 per minute Tamper output 100mA@30 VAC/VDC IP Rating IP65 Operating humidity 0~98% Operating temperature -4°~131° F (-20°~55° C) Housing Polycarbonate plastic Dimensions 6¹/8"x4¹5/16"x4¹1/2" (155x178x115 mm) 6¹/8"x7"x4¹/2" (155x178x115 mm)	Alarm inputs				
draw (max.) Strobe Both N/A 50mA@12VDC Siren volume 115dB Speaker rating 20W Peak Custom message WAV or MP3 format, up to 2MB Upload interface Micro-USB Strobe flash rate N/A 60 per minute Tamper output 100mA@30 VAC/VDC IP Rating IP65 Operating humidity 0~98% Operating temperature -4°~131° F (-20°~55° C) Housing Polycarbonate plastic Dimensions 6¹/8"x4¹5/16"x4¹1/2" (155x178x115 mm) Company the plastic of the properties of the plastic of the plasti	Audio in		Audio input voltage cannot exceed 2V		
(max.) Both N/A 1050mA@12VDC Siren volume 115dB Speaker rating 20W Peak Custom message WAV or MP3 format, up to 2MB Upload interface Micro-USB Strobe flash rate N/A 60 per minute Tamper output 100mA@30 VAC/VDC IP Rating IP65 Operating humidity 0~98% Operating temperature -4°~131° F (-20°~55° C) Housing Polycarbonate plastic Dimensions 6¹/8"x4¹5/16"x4⁴1/2" (155x178x115 mm) (155x178x115 mm)	Current Siren		1A@12VDC		
Siren volume 115dB Speaker rating 20W Peak Custom message WAV or MP3 format, up to 2MB Upload interface Micro-USB Strobe flash rate N/A 60 per minute Tamper output 100mA@30 VAC/VDC IP Rating IP65 Operating humidity 0~98% Operating temperature -4°~131° F (-20°~55° C) Housing Polycarbonate plastic Dimensions 6¹/8"x4¹5/16"x4⁴1/2" (155x178x115 mm) 6¹/8"x7"x4⁴/2" (155x178x115 mm)	draw	Strobe	N/A	50mA@12VDC	
Speaker rating 20W Peak Custom message WAV or MP3 format, up to 2MB Upload interface Micro-USB Strobe flash rate N/A 60 per minute Tamper output 100mA@30 VAC/VDC IP Rating IP65 Operating humidity 0~98% Operating temperature -4°~131° F (-20°~55° C) Housing Polycarbonate plastic Dimensions 6¹/8"x4¹5/16"x4¹/2" (155x126x115 mm) (155x178x115 mm)	(max.)	Both	N/A	1050mA@12VDC	
Custom message WAV or MP3 format, up to 2MB Upload interface Micro-USB Strobe flash rate N/A 60 per minute Tamper output 100mA@30 VAC/VDC IP Rating IP65 Operating humidity 0~98% Operating temperature -4°~131° F (-20°~55° C) Housing Polycarbonate plastic Dimensions 6¹/8"x4¹5/16"x4¹/2" (155x126x115 mm) (155x178x115 mm)	Siren volume		115dB		
Upload interface Micro-USB Strobe flash rate N/A 60 per minute Tamper output 100mA@30 VAC/VDC IP Rating IP65 Operating humidity 0~98% Operating temperature -4°~131° F (-20°~55° C) Housing Polycarbonate plastic Dimensions 6¹/8"x4¹5/16"x4¹1/2" (155x178x115 mm) 6¹/8"x7"x4¹/2" (155x178x115 mm)	Speaker rating		20W Peak		
Strobe flash rate N/A 60 per minute Tamper output 100mA@30 VAC/VDC IP Rating IP65 Operating humidity 0~98% Operating temperature -4°~131° F (-20°~55° C) Housing Polycarbonate plastic Dimensions 6¹/8"x4¹5/₁6"x4¹/₂" (155x126x115 mm) (155x178x115 mm)	Custom message		WAV or MP3 format, up to 2MB		
Tamper output 100mA@30 VAC/VDC IP Rating IP65 Operating humidity 0~98% Operating temperature -4°~131° F (-20°~55° C) Housing Polycarbonate plastic Dimensions 6¹/8"x4¹⁵/¹6"x4¹/2" (155x178x115 mm) 6¹/8"x7"x4¹/2" (155x178x115 mm)	Upload interface		Micro-USB		
IP Rating	Strobe flash rate		N/A	60 per minute	
Operating humidity 0~98% Operating temperature -4°~131° F (-20°~55° C) Housing Polycarbonate plastic Dimensions 6¹/₀"x4¹⁵/₁₀"x4¹½" (155x126x115 mm) 6¹/₀"x7"x4¹/₂" (155x178x115 mm)	Tamper output		100mA@30 VAC/VDC		
Operating temperature -4°~131° F (-20°~55° C) Housing Polycarbonate plastic Dimensions 6¹/₀"x4¹⁵/₁₀"x4¹½" (155x126x115 mm) (155x178x115 mm)	IP Rating		IP65		
temperature -4 - 2131 F (-20 - 55 ° C) Housing Polycarbonate plastic Dimensions 61/8"x415/16"x41/2" (155x126x115 mm) (155x178x115 mm)	Operating humidity		0~98%		
Dimensions 61/8"x415/16"x41/2" 61/8"x7"x41/2" (155x126x115 mm) (155x178x115 mm)	. •		-4°~131° F (-20°~55° C)		
(155x126x115 mm) (155x178x115 mm)	Housing		Polycarbonate plastic		
Weight 1-lb 13-oz (812g) 2-lb 2-oz (957g)	Dimensions			+ , 0 · · · · · · · · · · · · · · · · · ·	
1 9/	Weight		1-lb 13-oz (812g)	2-lb 2-oz (957g)	

^{*}Replace "x" with the first letter of the desired LED lens color – amber, blue, clear, or red.

SECO-LARM® U.S.A., Inc.

16842 Millikan Avenue, Irvine, CA 92606

Phone: (949) 261-2999 | (800) 662-0800 **Fax:** (949) 261-7326 **Website:** www.seco-larm.com **Email:** sales@seco-larm.com



Notification Priority



Available Models

SH-816S-SMQ/x & SM-816S-BMQ: 4-in-1 Multi-Purpose Siren/Strobe

